


3.2x2.5 SMD Crystal

FEATURE

- Rugged AT-cut crystal construction.
- Miniature 3.2×2.5mm ceramic package.
- Designed for automatic mounting and reflow soldering.
- Embossed taping specification.
- Pb-free and RoHS/Green compliant.

APPLICATIONS

- Ideally suited designed for Bluetooth wireless communication sets, HDD, DSN, PDA, GPS, Digital Tuner, Wireless LAN and mobile phone.



Pb
Free

RoHS Compliant
Directive 2002/95/EC

Electrical Specifications 电气参数


型号	Holder Type	3.2x2.5mm Ceramic Surface Mount
频率范围	Frequency Range	12MHz to 54MHz
调整频差	Frequency Tolerance (ΔF) (at25℃)	±10ppm to ±30ppm
温度频差	Frequency Drift	±10ppm to ±30ppm※(See Notes)
工作温度范围	Operating Temperature Range	-20℃ ~ +70℃ / -40℃ ~ +85℃
储存温度范围	Storage Temperature Range	-40℃ ~ +85℃ / -55℃ ~ +125℃
老化	Aging (25℃)	±3ppm/ year max.
静电容	Shunt Capacitance (C0)	3pF max.
激励功率	Drive Level	10μW (100μW max.)
绝缘阻抗	Insulation Resistance (Rs)	500 Megaohms Minimum at D.C100V
负载电容	Load Capacitance (CL)	Suggested by customer

※Notes: ±10, ±20, ±30ppm (-20℃ to +70℃)
±20, ±30, ±50ppm (-40℃ to +85℃) or depends on customer


Equivalent Series Resistance and Mode of Operation 等效阻抗和振荡模式

Frequency Range 频率范围	ESR (Ω) 等效阻抗	Mode 振荡模式
12.000MHz ≤ f < 16.000MHz	100Ω max	Fundamental
16.000MHz ≤ f < 20.000MHz	80Ω max	Fundamental
20.000MHz ≤ f < 24.000MHz	60Ω max	Fundamental
24.000MHz ≤ f < 54.000MHz	40Ω max	Fundamental

Reflow Condition(回流焊条件)



Mechanical Dimensions 外型尺寸



Note: R2, R4 is connected with a cover
(Please connect with a GND or a power supply)

SZT

深圳市尚臻泰科技有限公司
电话: 0755-86097691
传真: 0755-86097692
网址: www.szttech.com