

HC-49US Crystal

FEATURE

- Resistance weld seal.
- A resistance weld completely sealed type.
- The tight frequency stability.
- Low cost.
- Versatile.
- Pb-free and RoHS/Green compliant.

APPLICATIONS

- Ideally suited designed for Set-Top Box/Multimedia, modems, clock/VCO multipliers, network adapter cards and remote control devices.

Electrical Specifications 电气参数

型号	Holder Type	HC - 49U/S
频率范围	Frequency Range	3.200 to 100.000 MHz ※(See Notes 1)
调整频差	Frequency Tolerance (ΔF) (at 25°C)	$\pm 10\text{ppm}$ to $\pm 30\text{ppm}$
温度频差	Frequency Drift	$\pm 10\text{ppm}$ to $\pm 30\text{ppm}$ ※(See Notes 2)
工作温度范围	Operating Temperature Range	-20°C ~ +70°C / -40°C ~ +85°C
储存温度范围	Storage Temperature Range	-40°C ~ +85°C/-55°C ~ +125°C
老化	Aging (25°C)	$\pm 3\text{ppm}/\text{year}$ Maximum
静电容	Shunt Capacitance (C0)	7pF maximum
激励功率	Drive Level	100 μW Typical
绝缘阻抗	Insulation Resistance (Rs)	500 Megaohms Minimum at D.C100V
负载电容	Load Capacitance (CL)	Suggested by customer

※Notes 1: For 2.5mm height, lowest frequency is 10 MHz.

For 2.8mm height, lowest frequency is 6 MHz.



※Notes 2: ± 10 , ± 20 , $\pm 30\text{ppm}$ (-20°C to +70°C)

± 20 , ± 30 , $\pm 50\text{ppm}$ (-40°C to +85°C) or depends on customer

Equivalent Series Resistance and Mode of Operation 等效阻抗和振荡模式

Frequency Range 频率范围	ESR (Ω) 等效阻抗	Mode 振荡模式
3.200 $\leq f <$ 3.579 MHz	250Max	基频 Fundamental
3.579 $\leq f <$ 4.000 MHz	150Max	Fundamental
4.000 $\leq f <$ 5.000 MHz	120Max	Fundamental
5.000 $\leq f <$ 6.000 MHz	100Max	Fundamental
6.000 $\leq f <$ 7.000 MHz	80Max	Fundamental
7.000 $\leq f <$ 10.000 MHz	60Max	Fundamental
10.000 $\leq f <$ 14.000 MHz	50Max	Fundamental
14.000 $\leq f <$ 20.000 MHz	40Max	Fundamental
20.000 $\leq f <$ 48.000 MHz	30/40 (BT cut) Max	Fundamental
35.000 $\leq f <$ 40.000 MHz	100Max	三次泛音 Third Overtone
40.000 $\leq f <$ 100.000 MHz	80Max	Third Overtone

Reflow Condition(回流焊条件)




Pb Free

RoHS Compliant
Directive 2002/95/EC


Mechanical Dimensions 外型尺寸

S: TWO LEADS (两引线) UNIT (单位): mm (毫米)



UNIT (单位): mm (毫米)
H: S=3.30mm MAX
S2=2.0mm MAX
S3=2.5mm MAX
L: 13.2mm or 20.0mm Typical
(For Taping, only 20.0mm suitable)

SB: THREE LEADS (三引线) UNIT (单位): mm (毫米)



UNIT (单位): mm (毫米)
H: S=3.30mm MAX
S2=2.0mm MAX
S3=2.5mm MAX
L: 13.2mm or 20.0mm Typical
(For Taping, only 20.0mm suitable)



深圳市尚臻泰科技有限公司
电话: 0755-86097691
传真: 0755-86097692
网址: www.sztech.com